

GASOLINE GENERATOR - 3000rpm
Technical Data-Open Type

Generator		HY9900LE
Rated Power	kVA	6.5
Max. Power	kVA	7.2
Phase/Wire		1 phase / 2 wires
Voltage	V	220
Voltage fluctuation		±1%
Frequency	Hz	50
Frequency fluctuation		±5%
Current	A	31.2
Display		LED5
Fuel tank capacity	L	25
Fuel Consumption	L/h	4.5
Sound level @7m	dBA	<80
Battery Charge	V	12
Engine		IC460
Engine type		4 stroke, air-cooled gasoline, OHV type
Power	hp	17.5
Compression ratio		9.4:1
Bore*Stroke		92*69
Number of cylinder		1
Start		Electric
Displacement	cc	459
Oil capacity	L	1.1
Alternator		AL7
Power	kW	7.0
Power Factor		1
Voltage Regulator		AVR
Dimension and weight		
Net weight	kg	85
Gross weight	kg	
Machine size (L*W*H)	mm	685x512x550
Loading Capacity FCL20/40'HQ	mm	96/268



Optional Accessories



ATS control box (50A)



Remote controller



Push wheel kit

Electrical and Mechanical standards

- 1 phase (2x16A European sockets)
- LED 5 Displays: voltage, current, frequency, power, running time
- Earth connection
- ATS connector
- Key electric start
- Integrate steel tank coated with electrostatic paint
- Solid built and strong frame with anti-vibration and electrostatic coated
- Mechanical transmission: direct drive with a coaxial coupling

Other standards

- Available working conditions:
- Climate : tropical hot
 - Environmental temperature: 0-40°C
 - Humidity: 0-85%

Recommended spare part



Air filter core



Fuel filter element